

Enclosures & Cabinets for Special Requirements comercial@delvalle.es | www.delvallebox.com

MODULAR DISTRIBUTION WALL CABINETS LUXOR SERIES [P66]







We offer over **45 years** providing solutions to demanding customers who require very specific characteristics and behaviour according to the sector and their needs.

HIGH STANDARD OF QUALITY AND SERVICES

We only use materials provided by companies who offer the very **highest quality**, suitable and certified products. Our success is due to top quality assurance: ISO 9001, SGS, UL, TÜV, ISO 14000 and Ohsas 18001.

WHEREVER YOU GO

We are committed to working closely with our customers, providing them with **exceptional service** and offering an advanced and extensive range of products with very competitive prices.

CUSTOMIZE TOTALLY YOUR ENCLOSURE

Our production systems can give custom-made solutions **on demand.** Every colour from RAL chart is available to be personalized. A variety of protection standards thanks to our own painting facilities.

CONTACT US Confidentiality, reliability & quality

www.delvallebox.com comercial@delvalle.es +34 945 601 381

ALSO ONLINE

Please contact our technical sales department

A team of professionals with high experience and ability to solve all your queries





MODULAR DISTRIBUTION WALL CABINETS LUXOR SERIES 1966



Examples



Most Capacity Module in the Market

Robust and compact enclosure. Designed for wall mounted installations up to 472 modules for differential placement and circuit breakers. Compact enclosure for perfect sealing and resistance with drainage channel, polyurethane joint, concealed hinges and double-bit locks in A316 stainless steel.They include a protective Im that prevents scratches and abrasions during handling.

The rows are standard tops 150 mm high.

The transparent polycarbonate door combines high impact resistance (250 times stronger than glass) with excellent re resistance (UL94).With UV protection and suitable for outdoor applications.

Easy opening by smooth-turning locks, maximum opening of the doors (up to 120°), maximum working width for your assemblies, easily removable, polished surface, great performance.

Luxor series is also available in mild steel (painted). We also have embedded enclosures (Bally type).

FOR MORE INFORMATION CLICK HERE



MODULAR DISTRIBUTION WALL CABINETS LUXOR SERIES [P66]



Specially designed for all types of low-voltage switchboards, secondary or tertiary terminals and industrial environments. Also for residential, tertiary and industrial environments up to 1000A.

For environments where a esthetics is required and also durability and superior cleaning for painted enclosures or outdoor installations.




- Properties blind door:
 - IP66 (IP55 for 2 doors) according to IEC EN 62208 and EN 60529.
 - Degree resistance IK10 according to IEC 62208 and EN 50102.
 - o UL Nema 4x, 12, 3r, 1. File N° E342220.
- Properties transparent polycarbonate door:
 - o IP55 according to IEC EN 62208 and EN 60529.
 - Degree IK7 resistance according to IEC 62208 and EN 50102.
 - o Light transmission of 89% and protection from UV rays.
 - o Resistance to fire: UL94.
 - Fire classification: BS476 part 7, class IA (5 and 6 mm).
- A system which allows making distributions according to EN 60439-1 standard.
- Manufactured following EU low voltage ruling 2014/35/UE.
- Materials intended to come into contact with food EC 1935/2004 and RoHs compliant.
- Maximum voltage 1000 V.
- Temperature resistant: -40°C +100°C (short time +160°C).
- Option silicone gasket: from -60°C to +180°C (short time up to +350°C).


- Wide view of the modules.
- Easy mounting on DIN rail.
- They are designed with different dimensions of width and depth to allow total exibility in their facilities.
- Supports up to 1000 A and allow sealing to IP66 (on request and with full doors).
- Two options: blind door or transparent polycarbonate door.
- Delvalle made by order any size that suits your needs, including holes and drills on both doors and/or walls.

- Made to measure based on your needs.
- Possibility of two doors (from 800x600).
- 170° hinge that allows maximum opening for easy access to the cabinet without removing the door.
- Plinths/base.
- Metal legs.
- Wall support (not included in the standard model).
- Transparent door with safety glass.
- Manufactured in stainless steel AISI 316L EN 14404.
- Mounting plate insulation (bakelite) or stainless steel.
- EMC version according to 2014/30/UE of electromagnetic compatibility.



MODULAR DISTRIBUTION WALL CABINETS LUXOR SERIES [P66]







CLICK HERE TO DOWNLOAD THE FILES CAD - PLANS - CERTIFICATES



REFERENCES I DOOR

REFERENCES		DIMENSIONS (mm)										
BLIND DOOR	POLYCARBONATE DOOR	HEIGHT -A-	WIDTH -B-	DEPTH -C-	ROWS	MODULES BY ROW	total Modules	INSIDE HEIGHT	INSIDE WIDTH	INSIDE DEPTH	MACHINABLE AREA	
											DOOR	SIDE
MVAB302015Q	MVAB302015TQ	300	200 300	155	2	3	6	237	6	135	207×70	270×105
MVAB383015Q	MVAB383015TQ	380			2	9	18	317	18	135	287×170	350×105
MVAB383021Q	MVAB383021TQ	380	300	210	2	9	18	317	18	190	287×170	350×160
MVAB603815Q	MVAB603815TQ	600	380	155	4	13	52	537	52	135	507×250	570×105
MVAB603821Q	MVAB603821TQ	600	380 400 500 600	210	4	13	52	537	52	190	507×250	570×160
MVAB404021Q	MVAB404021TQ	400			2	15	30	337	30		307×270	370×160
MVAB504021Q	MVAB504021TQ	500			3	15	45	437	45		407×270	470×160
MVAB505021Q	MVAB505021TQ	500			3	20	60	437	60		407×270	470×160
MVAB705021Q	MVAB705021TQ	700			4	20	80	637	80		607×370	670×160
MVAB605021Q	MVAB605021TQ	600			4	20	80	537	80		507×370	570×160
MVAB606021Q	MVAB606021TQ	600			4	26	104	537	104		507×470	570×160
MVAB806030Q	MVAB806030TQ	800	600 800 1000 1200	- 300	5	26	130	737	130	280	707×470	770×250
MVAB808030Q	MVAB808030TQ	800			5	37	185	737	185		665×630	770×250
MVAB108030Q	MVAB108030TQ	1000			6	37	222	937	222		865×630	970×250
MVAB128030Q	MVAB128030TQ	1200			8	37	296	37	296		1065×630	1170×250
MVAB101030Q	MVABI01030TQ	1000			6	48	288	937	288		865×830	970×250
MVAB121030Q	MVAB121030TQ	1200			8	48	384	1137	384		1065×830	1170×250
*MVAB121230Q	*MVAB121230TQ	1200			8	59	472	1146	472		1006×976	1170×240
*MVAB101230Q	*MVABI01230TQ	1000			6	59	354	946	354		806×976	970×240
Version: Normative UL - Nema		Add "UL" to the reference. Ex "MVAB302015QUL"										

* Closing lever. Separation depth plate 20mm

REFERENCES 2 DOORS

REFERENCES		DIMENSIONS (mm)										
BLIND DOOR	POLYCARBONATE DOOR	HEIGHT -A-	WIDTH -B-	DEPTH -C-	ROWS	MODULES BY ROW	total Modules	INSIDE HEIGHT	INSIDE WIDTH	INSIDE DEPTH	MACHINABLE AREA	
											DOOR	SIDE
MVAB806030DQ	MVAB806030DTQ	800	600 800	300	5	18	90	746	546	270	260 × 125	260 × 130
MVAB808030DQ	MVAB808030DTQ	800			5	30	150	746	746		260 × 225	260 × 230
MVAB108030DQ	MVAB108030DTQ	1000			6		180	946			360 × 225	360 × 230
MVAB128030DQ	MVAB128030DTQ	1200			8		240	1146			460 x 225	460 × 230
MVAB101030DQ	MVABI01030DTQ	1000	1000		6	- 41	246	946	946		360 × 325	360 × 330
MVAB121030DQ	MVAB121030DTQ	1200			8		328	1146			460 x 325	460 × 330
MVAB121230DQ	MVAB121230DTQ	1200		8	52	416	1146	1146		460 × 425	460 × 430	
Version: Normative UL - Nema		Add "UL" to the reference. Ex "MVAB302015QUL"										

Separation depth plate 20mm





Consult us without obligation

Confidentiality, reliability & quality

DELVALLE OFFERS CUSTOMIZED SOLUTIONS

www.delvallebox.com comercial@delvalle.es +34 945 601 381 ALSO ONLINE

FOR MORE INFORMATION CLICK HERE





Consult us without obligation

Confidentiality, reliability & quality

DELVALLE OFFERS CUSTOMIZED SOLUTIONS

www.delvallebox.com comercial@delvalle.es +34 945 601 381 ALSO ONLINE

► FOR MORE INFORMATION CLICK HERE







Enclosures & Cabinets for Special Requirements





Paso del Prao, 6. 01320 Oyón (Álava). Spain P. +34 945 601 381 www.delvallebox.com - comercial@delvalle.es Contact us, we will be available at any time





