

comercial@delvalle.es | www.delvallebox.com

PAINTED GALVANIZED STEEL WALL CABINET





WE PUT AT YOUR DISPOSAL

We offer over **45 years** providing solutions to demanding customers who require very specific characteristics and behaviour according to the sector and their needs.

HIGH STANDARD OF QUALITY AND SERVICES

We only use materials provided by companies who offer the very **highest quality**, suitable and certified products. Our success is due to top quality assurance: ISO 9001, SGS, UL, TÜV, ISO 14000 and Ohsas 18001.

WHEREVER YOU GO

We are committed to working closely with our customers, providing them with **exceptional Service** and offering an advanced and extensive range of products with very competitive prices.

Our production systems can give custom-made solutions **on demand.** Every colour from RAL chart is available to be personalized. A variety of protection standards thanks to our own painting facilities.



CONTACT US

Confidentiality, reliability & quality

www.delvallebox.com comercial@delvalle.es +34 945 601 381

ALSO ONLINE



Please contact our technical sales department

A team of professionals with high experience and ability to solve all your queries





PAINTED GALVANIZED STEEL WALL CABINET LUXOR SERIES [P66]




The Manufacture of the Stainless Steel Monobloc Gives 100% Sealing and Maximum Resistance

The painted galvanized steel enclosures Luxor Series, are characterized by its robust design and surface finish in RAL 7035. Easy opening with chrome closures, smoothly turning, maximum flexibility and opening doors (up to 120°) with stainless steel hinges. Maximum Operating amplitude for the mounting and easily removable.

It has all the necessary measures to ensure their safety in electrical installations in outdoor facilities approvals.

→ FOR MORE INFORMATION CLICK HERE



PAINTED GALVANIZED STEEL WALL CABINET LUXOR SERIES [P66]



APPLICATIONS

Specially designed for outdoor environments where weather conditions are bad, such as the maritime sector, or for street lighting applications or services on railway lines, given its advantages of durability and strength.



CHARACTERISTICS

- The manufacture of the stainless steel monobloc gives 100% sealing and maximum resistance.
- With flushing channel that avoids any contact with liquids, polyurethane joints and hidden hinges.
- The standard control panel comes with stainless steel double-bit locking handles.
- Delvalle supplies any measurements required including custom built holes and cut outs both for the door and enclosure.
- Approved for outdoor installations.
- Stainless steel hinges.
- Wide range of accessories.
- Galvanized steel painted RAL 7035.



NORMS

- IEC 60529 norm. IP66 degree.
- UL approval Nema 1, 3r, 4 and 12.
 N° File E342220.
- IEC 62262 norm, Maximum IK10 resistance.
- 2014/35/UEDirective. Low voltage ruling.
- IEC 62208 norm.
- Maximum voltage 1000 V.






OPTIONS

- Custom made based on your needs.
- Possibility of two doors.
- 170° hinge that allows maximum opening for easy access to the cabinet without removing the door.
- Socles.
- Metal legs.
- Wall support (not included in the standard model).
- Transparent polycarbonate door.
- Transparent safety glass door.
- Mounting plate insulation (bakelite) or stainless steel.
- EMC version according to 2014/30/UE of electromagnetic compatibility.
- Switchboard graffiti-proof paint.



PAINTED GALVANIZED STEEL WALL CABINET LUXOR SERIES [P66]













REFERENCES I DOOR

BLIND DOOR	POLYCARBONATE DOOR	POLYCARBONATE DOOR + INSIDE DOOR	HEIGHT -A-	WIDTH -B-	DEPTH -C-	ACCESS -GxH-	INSIDE DEPTH -D-	MACHINABLEAREA		PLAQUE	WEIGHT	VOL.
								DOOR	LATERAL	MEASUREM. -FxE-	(Kg)	(m³)
MVGB302015	MVGB302015T	MVGB302015TC	300	200	155	260 × 153	125	220 × 76	270 × 125	264×147	4,65	0,01
MVGB383015	MVGB383015T	MVGB383015TC	380	300	155	340 × 253	125	300 × 176	350 × 125	344×247	7,68	0,02
MVGB383021	MVGB383021T	MVGB383021TC	380	300	210	340 × 253	180	300 × 176	350 × 180	344×247	8,57	0,03
MVGB404021	MVGB404021T	MVGB404021TC	400	400	210	360 × 353	180	320 × 276	370 × 180	364×347	11,12	0,04
MVGB504021	MVGB504021T	MVGB504021TC	500	400	210	460 × 353	180	420 × 276	470 × 180	464×347	13,51	0,05
MVGB505021	MVGB505021T	MVGB505021TC	500	500	210	460 × 453	180	420 × 376	470 × 180	464×447	16,2	0,06
MVGB604021	MVGB604021T	MVGB604021TC	700	500	210	660 × 453	180	620 × 376	670 × 180	664x447	21,55	0,08
MVGB605021	MVGB605021T	MVGB605021TC	600	400	210	560 × 353	180	520 × 276	570 × 180	564×347	15,74	0,06
MVGB606021	MVGB606021T	MVGB606021TC	600	500	210	560 × 453	180	520 × 376	570 × 180	564×447	18,88	0,07
MVGB606030	MVGB606030T	MVGB606030TC	600	600	210	560 × 553	180	520 × 476	570 × 180	564×547	22	0,08
MVGB705021	MVGB705021T	MVGB705021TC	800	600	300	760 × 553	270	720 × 476	770 × 270	764×547	31,35	0,16
MVGB806030	MVGB806030T	MVGB806030TC	800	800	300	760 × 753	270	720 × 676	770 × 270	764×747	41,5	0,21
MVGB808030	MVGB808030T	MVGB808030TC	1000	800	300	960 × 753	270	920 × 676	970 × 270	964×747	50,69	0,26
MVGB108030	MVGB108030T	MVGB108030TC	1200	800	300	1160 × 753	270	1120 × 676	1170 × 270	1164×747	59,47	0,31
MVGB101030	MVGB101030T	MVGB101030TC	1000	1000	300	960 × 953	270	920 × 876	970 × 270	964x947	61,17	0,32
*MVGC128030	MVGC128030T	MVGC128030TC	1200	1000	300	1090 × 890	275	1000 × 800	1190 × 265	1070×870	78.82	0,46
*MVGC121030	MVGC121030T	MVGC121030TC	1000	1200	300	890 × 1090	275	800 × 1000	990 × 265	870×1070	78,76	0,39
*MVGC121230	MVGC121230T	MVGC121230TC	1200	1200	300	1000 × 1000	275	1000 × 1000	1190×265	1070×1070	92,09	0,39
Version Norme	Add "UL" to reference. Ex. "MVAB302015UL"											

^{*}Tribeca Design Separation plaque fund 20mm



REFERENCES 2 DOORS

REFERENCES										
2 BLIND DOORS	HEIGHT -A ⁻	WIDTH -B-	DEPTH -C-	ACCESS -GxH-	INSIDE DEPTH -D-	MACHINAB	PLAQUE MEASUREM.			
						DOOR	LATERAL	-FxE-		
MVGB806030D	800	600	300	746 × 546	270	720×217.5 y 720×173.5	720×240	740×540		
MVGB808030D	800	800	300	746 × 746	270	720×317.5 y 720×273.5	720×240	740×740		
MVGB108030D	1000	800	300	946 × 746	270	920×317.5 y 920×273.5	970×240	940×745		
MVGB128030D	1200	800	300	1146 × 746	270	1120×317.5 y 1120×273.5	1170×240	1140×745		
MVGB101030D	1000	1000	300	946 × 946	270	920×417.5 y 920×373.5	970×240	940×940		
MVGB121030D	1200	1000	300	1146 × 946	270	1120×617.5 y 1120×573.5	1170×240	1140×945		
MVGB121230D	1200	1200	300	1146 × 1146	270	1120×717.5 y 1120×673.5	1170×240	1140×1140		
Option: Polycarbonate door				Add "T" to reference, Ex. "MVAB806030DT"						
Option: Polycarbonate door + Inside door				Add "TC" to reference. Ex. "MVAB806030DTC"						
Version Norme UL Ner	d I		Add "UL" to reference. Ex. "MVAB302015UL"							
Option: IP66			Add "66" to reference, Ex. "MVAB806030D66"							

Separation plaque fund 20mm







CUSTOMIZED ENCLOSURE SOLUTIONS DELVALLE

Delvalle has more than 50 years of experience using the latest technology to implement and obtain the most innovative products on offer to all our customers. Delvalle is an ideal partner, combining an advanced and wide range of products at very competitive prices.

The customized manufacture of all electrical enclosures and cabinets Delvallebox is carry out with the most advanced technical methods and with the precision and consciousness of a craftsman. This makes the difference from competitors and is the best way to gain our customers' trust.

In Delvallebox we bear in mind that customers perceive the quality very clearly. In every product (for instance, in the cabinets here presented) safety and useful solutions are what customers value most.



STAINLESS STEEL INDUSTRIAL ENCLOSURES



OUTDOOR ELECTRICAL ENCLOSURES



GLOBAL ELECTRICAL SOI UTIONS FOR URBAN AREAS



GALVANIZED STEEL ELECTRICAL ENCLOSURES






SLOPED ROOF ENCLOSURES - HYGIENIC

ATEX INDUSTRIAL ENCLOSURES



INDUSTRIAL ENCLOSURES IP66, IP67, IP68 AND IP69K

Buy direct from manufacturer of custom made IP66, IP67, IP68 and IP69K heavy duty industrial and waterproof electrical enclosures AISI 304L and 316L made by standard IEC 60529. Delvalle has tested all sizes and dimensions of waterproof enclosures according to EN 60529:2018. All weather resistant enclosures are more than simply rainproof, they meet a minimum of Nema 4X and IP66, IP67, IP68 and IP69k requirements to ensure your electronics are protected. From Juntion boxes to industrial enclosures, Delvalle weatherproof enclosures offer a wide range of sizes and styles to keep your project waterproof.



CABLE GLANDS FOR ELECTRICAL ENCLOSURES

CLIMATE CONTROL COOLING FOR ENCLOSURES











Paso del Prao, 6.01320 Oyón (Álava). Spain Phone +34 945 601 381 comercial@delvalle.es | www.delvallebox.com Contact us, we will be available at any time







